

# Product list

## Superconducting wires

NbTi SC Wire	WIC	Dimention(mm): 1.85*1.3~3.39*1.95 Critical Current: 200A~2000A(@4T,4.2K) Cu: SC Ratio:5~20
	Monolith	Round Dimention(mm): 0.4~1.8 Critical Current: 200A~2000A(@4T,4.2K) Cu: SC Ratio:1~10 Ranctangular Dimention(mm): 1.0*0.6~1.8*1.2 Critical Current: 200A~2000A(@4T,4.2K) Cu: SC Ratio:1~10
	Low AC Loss	Dimention(mm): 0.7~1.0 Critical Current: 400A~1000A(@4T,4.2K) Number of Filaments: 10000~50000
Nb <sub>3</sub> Sn SC Wire	Internal Tin	Dimention(mm): 0.7~1.6 Critical Current: 200A~800A(@12T,4.2K) Cu:SC Ratio: 0.8~1.2
	Bronze Route	Dimention(mm): 0.7~1.0 Critical Current: 200A~400A(@12T,4.2K) Cu:SC Ratio: 0.8~1.2
MgB <sub>2</sub> SC Wire		Dimention(mm): 1.0~1.5 Critical Current: 200A~500A(@4T,20K) Non-SC:SC Ratio: 6~7

